Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-11. (Canceled)
- 12. (Currently Amended) An optical recording medium comprising:

an active layer of inorganic material able to undergo deformations due to the effect of an optical radiation, presenting a front face designed to receive an optical radiation during writing operations, and a rear face;

and a medium comprising an additional metal layer arranged on in contact with the rear face of the active layer;

wherein the inorganic material of the active layer is a tellurium and zinc alloy consisting of <u>only</u> an atomic percentage of between 60% and 70% of zinc and between 30% and 40% of tellurium.

- 13. (Previously Presented) Recording medium according to claim 12, wherein the additional metal layer has a thickness comprised between 9 nanometers and 12 nanometers.
- 14. (Previously Presented) Recording medium according to claim 12, wherein the material of the additional metal layer is taken from the group comprising aluminium, gold, silver and copper.
 - 15. (Canceled)
- 16. (Previously Presented) Recording medium according to claim 12, wherein the alloy comprises 65% of zinc and 35% of tellurium.
- 17. (Previously Presented) Recording medium according claim12, wherein the active layer has a thickness comprised between 15 nanometers and 50 nanometers.

- 18. (Previously Presented) Recording medium according to claim 12, comprising a semi-reflecting layer arranged on the front face of the active layer and having a thickness comprised between 4 nanometers and 10 nanometers.
- 19. (Previously Presented) Recording medium according to claim 18, wherein the semi-reflecting layer is made of metal taken from the group comprising aluminium, gold, silver, copper, zinc, titanium, nickel and alloys thereof.
- 20. (Previously Presented) Recording medium according to claim 12, comprising a protective layer made of polymer material on the rear face.
- 21. (Previously Presented) Recording medium according to claim 20, wherein the protective layer is polydimethylsiloxane-based and has a thickness comprised between 10 micrometers and 100 micrometers.
- 22. (Previously Presented) Recording medium according to claim 20, wherein the protective layer is deformable.
- 23. (New) Recording medium according to claim 12, wherein the additional metal layer has a front face, in contact with the rear face of the active layer, and a rear face that constitutes an exposed rear face of the optical recording medium.
- 24. (New) Recording medium according to claim 12, wherein the recording medium consists of only a substrate, a single active layer, and the additional metal layer.